

# **SAFETY DATA SHEET**

# 1. IDENTIFICATION

Product Name: ELIMINATOR 107 - Anti-Spatter

Other means of identification: None

Supplier: HE&M Inc.

PO Box 1148

4065 South Main & Webb Mid America Industrial Park

Pryor, OK 74361

**Telephone:** (888) 729-7787

(918) 825-4821

**Fax:** (918) 825-4824

In case of Emergency: INFOTRAC

US and Canada (800) 535-5053

Outside the US or Canada

+01-352-323-3500

**Recommended Use:** Industrial Metalworking Fluid. See product data sheet for a detailed description of

recommended use.

# 2. HA7ARDS IDENTIFICATION

GHS Classification This material is classified in accordance with OSHA Hazard Communication Standard (29

CFR 1910.1200).

Classification Skin corrosion/irritation - Category 2A Eye irritation/damage - Category 2

**GHS** Label

Hazard pictogram

Signal word Warning

Hazard Statement H373 – May cause damage to organs through prolonged or repeated exposure.

H319 – Causes serious eye irritation.

H315 – Causes skin irritation.

Precautionary statements

Prevention P260 – Do not breathe dust/fume/gas/mist/vapors/spray.

P264 – Wash thoroughly after handling

P270 – Do not eat, drink or smoke when using this product.

P280 – Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician.

P302+P352 – IF ON SKIN: Wash with plenty of water.

Response P305+P351+338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 – Get medical advice/attention if you feel unwell.

P337+P313 – If eye irritation persists: Get medical advice/attention. P362+P364 – Take off contaminated clothing and wash before reuse.

Storage Not Applicable



Disposal

P501 – Dispose of contents and container in accordance with all local, regional, national and international regulations.

# COMPOSITION/INFORMATION ON INGREDIENTS

# Substance / Mixture:

Components/Ingredients CAS No. % Range\*

 Triethanolamine
 102-71-6
 <5</td>

 Alkanolamide
 Trade Secret
 1 - 5

 Ethanolamines, 2,2'-iminobisethanol
 111-42-2
 <0.5</td>

Additional components, of which may or may not be present, in this mixture are not classified as hazardous to health or the environment and within the current knowledge of the manufacturer or supplier and current regulations, are required to be reported in this section.

Occupational exposure limits, if applicable and available, are listed in Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION.

### FIRST AID MEASURES

Eye Do not rub eyes. Irrigate with flowing water immediately and continuously for a minimum of

15 minutes. If wearing contact lenses remove first, if able. Seek medical assistance

immediately if irritation occurs.

Skin Thoroughly rinse contact areas with water and soap. If clothing or shoes are contaminated;

remove immediately and wash before using again. Seek medical attention immediately if

irritation occurs.

Ingestion DO NOT induce vomiting, unless directed to do so by appropriate medical personnel. Never

give anything by mouth to an unconscious person. If person is conscious, rinse out mouth

with water. Seek medical attention immediately.

Inhalation Contact a medical professional immediately. Effects of inhalation are not established. It is a

good practice to remove victim to fresh air and from further exposure when inhalation occurs. If patient experiences irritation to the respiratory system, dizziness, nausea, or unconsciousness, seek medical attention immediately. If breathing has stopped, assist ventilation with a mechanical device or mouth-to-mouth resuscitation. If irritation persists,

consult medical personnel.

Notes to Physician In case of inhalation of decomposition products in a fire, symptoms may be delayed. The

exposed person may need to be kept under medical surveillance for 48 hours. Treatment

should in general be symptomatic and directed to relieving any effects.

Most important symptoms or effects, acute and delayed

For more detailed information on health effects and symptoms see Section 11 -

TOXICOLOGICAL INFORMATION

Description of necessary first aid measures or specific treatments

Treatment should in general be symptomatic and directed to relieving any effects.

# FIRE FIGHTING MEASURES

<sup>\*</sup>Specific percentages of composition are being withheld as a trade secret.

<sup>\*</sup>Proprietary CAS numbers are being withheld as a trade secret.



Alcohol-resistant foam, dry chemical, and carbon dioxide are appropriate extinguishing Extinguishing Media

media.

Unsuitable Extinguishing Media Avoid using water jet.

Specific Hazards from Chemical Not known.

**Hazardous Combustion Products** Combustion products may include the following: oxides of carbon (CO, CO<sub>2</sub>), oxides of

nitrogen, and other undetermined byproducts of combustion.

Special Fire Fighting Instructions Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water

supply. Firefighters should use standard protective equipment and in enclosed spaces, self

- contained breathing apparatus (SCBA).

Contents in closed container, in a fire or if held at a high temperature for extended periods Unusual Fire or Explosion Hazards

of time, may cause a pressure increase and cause the container to burst.

### **ACCIDENTAL RELEASE MEASURFS** 6.

Personal Precautions, Protective Equipment, and Emergency

**Procedures** 

Spilled material may make surfaces slippery.

Wear suitable protective gear, such as: chemically protective gloves, eye protection,

chemically protective boots, and chemically protective clothing.

**Environmental Precautions** Dike spilled material to prevent spreading and any releases of this material to the

environment. DO NOT allow material to enter waterways or water systems.

Methods and Materials for Containment and Cleaning Up

Dike spilled material and soak up with inert absorbent material, such as: mops, sand, oil-dri, or fiber media. Dispose of material in accordance with all Federal, State and Local regulations. Do not touch or walk through spilt material. Avoid breathing vapor or mist.

Provide adequate ventilation.

#### HANDLING AND STORAGE 7.

Ensure adequate ventilation. Keep out of reach of children or individuals not educated Handling

> and familiar with the potential hazards of this material. Avoid contact with eyes. Do not ingest. Avoid prolonged or repeated contact with skin. Do not mix or contaminate with other chemicals. Do not eat, drink or smoke while using this product. Avoid high heat, flames, ignition sources, or UV light. Wear appropriate PPE, avoid breathing vapor or mist. Empty containers retain product residue and can be hazardous. Keep in the original container or an alternative made from a compatible material; keep closed when not in

use. Do not reuse original container.

Store in a closed, properly labeled container, in accordance with all regulations. Store in Storage

the original container, away from direct sunlight, and incompatible materials. Store at

temperatures below 100°F. Keep container tightly sealed when not in use.

### EXPOSURE CONTROLS / PERSONAL PROTECTION 8.

The level of protection and types of controls necessary will vary depending upon **Engineering Controls** 

potential exposure conditions. Showers, eyewash stations, and ventilation systems are

appropriate.

**Environmental Controls** Comply with applicable environmental regulations limiting discharge to air, water and

soil. Protect the environment by applying appropriate control measures to prevent or limit



emissions.

**Exposure Limit Values** 

Metalworking Fluids – Particulates **Not Otherwise Classified** 

OSHA - TWA

15 mg/m<sup>3</sup> (8 hour)

NIOSH - TWA REL (Recommended Exposure Limit)

0.5 mg/m<sup>3</sup> total particulate (10 hour / day; 40-hour work week)

Ethanolamines, 2,2'iminobisethanol

OSHA - PEL

15 ma/m<sup>3</sup> TWA (8 hours)

ACGIH - TLV

1 mg/m<sup>3</sup> TWA (8 hours) – Inhalable fraction and vapor

ACGIH - TLV triethanolamine (component)

5 mg/m<sup>3</sup> - TWA (8 hours)

Personal Protective Equipment

Eye / Face Protection If contact from spray or splashing is likely, safety glasses with side-shields are

recommended.

Skin Protection Wear suitable chemical resistant gloves while handling concentrate and water extended

product. Use of chemically resistant gloves is recommended when in contact for prolonged periods or by individuals whom are dermally sensitive. When the risk of skin exposure is high, chemical resistant aprons and/or impervious chemical suits and boots may be required. PPE for the body should be selected based on the potential for contact with the product and the potential risks involved if contact may occur.

Respiratory Protection The choice of respiratory protections is dependent upon the environment the product is

being used and the environment of the product is used in. Safety procedures should be

developed for all intended conditions of handling and use of this product.

Special Instructions for

Provide readily accessible eye wash stations and safety showers. Wash hands at the end of each work shift and before eating, smoking or using the toilet. Always observe good Protection and Hygiene

personal hygiene measures, such as washing after handling the material and before eating, drinking, or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be

cleaned. Practice good housekeeping.

#### PHYSICAL AND CHEMICAL PROPERTIES 9.

Appearance Blue Liquid Mild Odor Odor Odor Threshold Not Determined

9.50 - 10.50

Melting Point / Freezing Point Not Determined Initial Boiling Point and Boiling Range Not Determined

Flash Point Not Determined

Evaporation Rate (Butyl Acetate @ 25°C = 1) Not Determined

Flammability (solid, gas) Not Applicable

Upper Explosive Limit / Lower Explosive Limit Not Applicable Vapor Pressure (Water @ 20°C = 17.5 mmHg) Not Determined Vapor Density Not Determined

Relative Density (20°C) 0.99 - 1.01

Solubility Miscible Partition Coefficient (n-octanol / water) Not Determined



Auto-ignition Temperature Decomposition Temperature Viscosity Not Determined Not Determined Not Determined

# 10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended handling and storage conditions.

Incompatible Materials Keep away from acids. Prevent contact with strong oxidizing agents. Avoid use of

aluminum, copper, zinc, tin and/or brass alloys in contact with this material. Do not add

with nitrates/nitrites. Avoid contact with alkaline.

Conditions to Avoid Excess heat and sources of ignition

Hazardous decomposition During combustion carbon ma

materials

During combustion carbon monoxide may be formed. During combustion carbon dioxide may be formed. Decomposition releases nitrogen oxides. Combustion can lead to the

formation of ammonia.

Reactivity Not expected.

Other Information This mixture contains alkanolamines. Nitrites or other nitrosation compounds may react

with components in this material to form potentially carcinogenic nitrosamines.

# TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Skin Contact, Eye Contact

Potential Acute Health Effects

Eye Contact Causes serious eye irritation. Category 2A Skin Contact Causes skin irritation. Category 2

Inhalation Not determined. Inhalation of products of decomposition may cause health hazard.

Serious effects may be delayed after exposure. Repeated or prolonged exposure to

mist may produce respiratory tract irritation.

Ingestion May be harmful if swallowed.

Component Result Species Dose Exposure

 Alkanolamide
 LD50 Dermal LD50 Dermal Rabbit
 >2,000 mg/kg

 LD50 Oral
 Rat
 >5,000 mg/kg

 Triethanolamine
 LD50 Dermal Rabbit
 >2,000 mg/kg

 LD50 Oral
 Rabbit
 >2,000 mg/kg

LD50 Oral Rat 4,190 mg/kg
Ethanolamines, 2,2'- LD50 Dermal Rabbit >8,180 mg/kg
iminobisethanol

LD50 Oral Rat 620 mg/kg

Delayed / Chronic Health Effects

Eye Contact May cause delayed lung damage. Suspect cancer hazard. Overexposure may cause nervous system damage. Overexposure may cause kidney damage. May cause liver

disorder (e.g., edema, proteinuria) and damage. Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes. Exposure may damage liver and kidneys.

Suspected of damaging fertility. Possibly carcinogenic to humans.

Skin Contact Inhalation Ingestion

Skin Corrosion / Irritation Category 2
Eye Damage / Irritation Category 2A

Skin Sensitizer Mixture not determined
Respiratory Sensitizer Mixture not determined
Germ Cell Mutagenicity Mixture not determined
Teratogenicity Mixture not determined



Developmental Mixture not determined Fertility Mixture not determined Carcinogenicity Mixture not determined Reproductive Toxicity Mixture not determined Aspiration Toxicity Mixture not determined Specific Target Organ Toxicity -Mixture not determined Single Exposure

Specific Target Organ Toxicity -Mixture not determined Repeated Exposure

This mixture contains alkanolamines. Nitrites or other nitrosation compounds may react Additional information

with components in this material to form potentially carcinogenic nitrosamines.

### 12. **ECOLOGICAL INFORMATION**

**Aquatic Toxicity** Do not release into waterways, water systems, or land. Material is water soluble. May

cause adverse physical affects to aquatic organisms. Not expected to be toxic to

aquatic organisms. Not determined for classification under 1910.1200.

### **DISPOSAL CONSIDERATIONS** 13.

Disposal recommendations based on material as supplied. Disposal must be in accordance with all current applicable federal, state, and local laws and regulations, and material characteristics at time of disposal. Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty containers should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

The unused product, in our opinion, is not specifically listed by the EPA as a hazardous waste, nor is it formulated to contain materials which are listed as hazardous wastes. It does not exhibit the hazardous characteristics of ignitability, corrosivity, toxicity, or reactivity and is not formulated with contaminants as determined by the Toxicity Characteristic Leaching Procedure (TCLP). However, used product may be regulated.

### 14. TRANSPORT INFORMATION

Not Applicable **UN Number** Not Applicable **UN Proper Shipping Name** Transport Hazard Class Not Applicable Packing Group Not Applicable

**Environmental Hazards** Marine Pollutant - Not determined

Transportation in Bulk (Annex II of MARPOL

73/78 and IBC Code)

Special Precautions Spilled material may be a slip hazard.

U.S. DOT / Canadian TDG Not Regulated for shipping

IMO / IDMG Not determined ICAO / IATA Not determined ADR / RID Not determined

### 15. REGULATORY INFORMATION



**OSHA HAZARD COMMUNICATION STANDARD:** The hazard classifications of this substance / mixture were made congruent to the Occupational Safety and Health Standards, established in OSHA Regulation Standards 29 CFR 1910.1200.

Complies with the following national/regional chemical inventory requirements: TSCA, DSL, EINECS

**EPCRA SECTION 302:** This material contains no extremely hazardous substances.

EPA SARA Title III Section 311/312 (40 CFR 370) Hazard Classification: Acute health hazard, Chronic health hazard

EPA SARA Title III Section 313 (40 CFR 372): Alkanolamide Cas: 68603-42-9; Ethanolamines, 2,2'-iminobisethanol cas: 111-42-2

CLEAN AIR ACT (CAA): Triethanolamine

CLEAN WATER ACT (CWA): Not Applicable

California Proposition 65: Warning: The following ingredients present in the product are known to the state of California to cause

Cancer:

**Chemical Name**Ethanolamines, 2,2'-iminobisethanol

111-42-2

### 16. ADDITIONAL INFORMATION

Revision Date: January 28, 2019

Revision #: 3.0

Supersedes Revision #: 2.0

This SDS prepared for this substance / mixture was made congruent to the Occupational Safety and Health Standards, established in OSHA Regulation Standards 29 CFR 1910.1200.

**Disclaimer:** The information presented herein has been compiled from sources considered to be dependable and is accurate as of the date issued. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use are beyond our control, we make no warranty regarding the accuracy of such data or its suitability for any use or for any consequence of its use. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Safe handling and use remain the responsibility of the purchaser and the purchaser has the sole responsibility to determine the suitability of the materials for any use and the manner of user contemplated. We assume no responsibility for injury to the recipient or to third persons or for any damage to any property and the recipient assumes all such risks.

HMIS	Health	Flammability	Physical Hazard	PPE
	2	1	0	В
NFPA	Health	Flammability	Chemical Reactivity	Special Hazards
	2	1	0	None
				Known