

HE&M[®] ELIMINATOR

111 Turbo Drill

Eliminator 111- Turbo Drill contains FHW Technology, an advanced additive package designed to reduce Friction, Heat and Wear for exceptional tool life.

- 100% ultra synthetic oil free misting fluid
- Specially formulated for Drilling Applications
- Leaves little or no residue
- Provides corrosion protection
- Formulated to provide superior resistance to bacteria growth
- Safe to use on all metals and will not stain
- Does not irritate operator's hands
- Enhances tool life
- Keeps coolant fresher longer

Does Not Contain: Silicone, Chlorine, Sulfur, Phenols, Halogens

Refractometer Schedule:

DILUTION RATIO WATER TO CHEMICAL	BRIX SCALE			
	0 - 10	0 - 30	0 - 32	
1:1	Off Scale	11	12.5	
2:1	8.25	8	8.5	
3:1	6	5.5	6.5	
4:1	4.5	4.5	5	
5:1	4.0	4.0	4.5	
6:1	3.5	3.5	3.75	
7:1	2.5	2.75	3.25	
8:1	2.0	2.5	2.75	
9:1	1.75	2.0	2.5	
10:1	1.5	1.75	2.25	
11:1	1.25	1.5	2.0	
12:1	1.0	1.25	1.75	
13:1	0.80	1.5	1.62	
14:1	0.75	1.25	1.5	
15:1	0.5	1.0	1.25	
18:1	0.3	0.90	1.0	
20:1	0.15	0.80	0.90	

Suggested Dilution Ratio:
to be used as a misting fluid 15/20:1

NOTE: Always calibrate your refractometer to zero using your coolant water supply. Clean lens thoroughly, then apply water. Reading should be "0" (zero). If not, calibrate using the small set screw on the top or bottom of the refractometer.

Available In:

P-111000 1 Gallon
P-111001 4 Gallon Case
P-111005 5 Gallon Pail
P-111055 55 Gallon Drum
P-111275 275 Gallon Tote

Physical & Chemical Characteristics:

Appearance/Odor....Clear Liquid/Clean
Weight (lb/gal) 8.6
pH (@ 10:1 dilution) 9.5
Flash Point None

Address: P.O. Box 1148 Pryor OK 74362 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HE&M, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any product, at any time without notice and without incurring any obligations. Copyright 112800 HEM, Inc. All rights reserved.