

## 201 Synthetic

## Experience improved fluid stability and longevity with HE&M's enhanced line of Eliminator metalworking fluids.

- 100% synthetic oil free metalworking fluid
- Excellent corrosion protection
- Superior resistance to microbial degradation
- Oil rejecting formula
- Leaves minimal residue
- Provides quality finishes on machined parts
- Low foaming characteristics
- · Safe to use on all metals non staining

Operation	Cast Iron & Carbon Steels	High AlloySteels & Stainless Steel	Copper & Aluminum
Machining, Milling, Drilling, and Turning	1:24 (4%)	1:19 (5%)	1:24 (4%)
Form Milling and Sawing	1:19 (5%)	1:19 (5%) 1:16 (6%)	1:24 (4%) 1:19 (5%)
Grinding: ID, OD, Centerless	1:24 (4%)	1:19 (5%)	1:24 (4%)

Dilution Ratio	1:9 (10%)	1:16 (6%)	1:19 (5%)	1:24 (4%)	1:32 (3%)
Refractometer Reading	3.7	2.3	1.9	1.6	1.2

## Available In:

P-201000 1 Gallon
P-201001 4 Gallon Case
P-201005 5 Gallon Pail
P-201055 55 Gallon Drum
P-201275 275 Gallon Tote

## **Physical & Chemical Characteristics:**

Appearance/Odor....Clear Liquid/Mild Chemical Weight (lb/gal) 8.6
pH (concentrate) 9.4
pH (5% dilution) 9.0
Flash Point None

Address: P.O. Box 1148 Pryor OK 74362 • Toll Free: 888-729-7787 • Email: info@hemsaw.com