

## 203 Soluble Oil

## Experience improved fluid stability and longevity with HE&M's enhanced line of Eliminator metalworking fluids.

- Heavy-duty water soluble oil formula
- Contains no chlorine, nitrates, phenols or dimethlyl polysiloxane
- Excellent corrosion protection
- Provides quality finishes on machined parts
- Superior resistance to microbial degradation
- Low foaming characteristics
- Safe to use on all metals non staining

Operation	Cast Iron & Carbon Steels	High AlloySteels, Stainless Steel & Tool Steels	Aluminum & Nickel Alloys
Broaching, Tapping	1:24-1:19	1:9	1:39-1:32
	(4-5%)	(10%)	(2.5-3%)
Gear Shaping, Deep Drilling, Form Milling, Tapping Sawing	1:24-1:19 (4-5%)	1:19-1:16 (5-6%)	1:39-1:32 (2.5-3%)
Grinding: ID, OD,	1:24-1:19	1:32	1:32-1:24
Centerless	(4-5%)	(3%)	(3-4%)

Dilution Ratio	1:9 (10%)	1:16 (6%)	1:19 (5%)	1:24 (4%)	1:32 (3%)
Refractometer Reading	10.0	6.0	5.0	4.0	3.0

## Available In:

P-203000 1 Gallon
P-203001 4 Gallon Case
P-203005 5 Gallon Pail
P-203055 55 Gallon Drum
P-203275 275 Gallon Tote

## **Physical & Chemical Characteristics:**

Appearance/Odor....Amber Liquid/Mild Petroleum Weight (lb/gal) 7.6
pH (concentrate) 9.8
pH (5% dilution) 9.6
Flash Point 350°F

Address: P.O. Box 1148 Pryor OK 74362 • Toll Free: 888-729-7787 • Email: info@hemsaw.com