

HEM & M[®] ELIMINATOR

215 68 Slide & Way Oil

Eliminator 215 68 Slide & Way Oil is an ultra-premium slide and way lubricant designed to provide high load carrying performance and a long lasting, uniform coating on machine tool lubrication systems.

Formulated with highest quality base oils and high performance anti-friction and corrosion additives, they meet the requirements of high speed high load carrying machine tools.

Eliminator 215 68 Slide & Way Oil has excellent oxidation stability and helps reduce maintenance and downtime, minimizes deposits and contributes to system cleanliness. Because of the unique additive chemistry and the premium oils ability to resist oxidation, the byproducts caused from oxidation the lead to varnish are substantially reduced when compared to conventional oils. Falcon's slide way oils are optimized to provide separability and demulsify from aqueous coolants for easy removal, while minimizing the corrosive effective of high pH coolants on lubricated surfaces. Designed for lasting lubrication in the presence of water or water based metalworking fluids.

Applications:

Horizontal slideways on small to medium sized machine tools.

Suitable for flood application in large machines.

Can be used as a moderate duty hydraulic fluid.

Helps reduce the deterioration of sliding surfaces in the presence of aqueous coolants.

Machines operating a wide range of temperatures and components using various metallurgies. Numerically Controlled (NC) Machine Tools.

Eliminates Slip-Stick and allows for consistent and accurate machining.



Available In:

P-215000	1 Gallon
P-215001	4 Gallon Case
P-215005	5 Gallon Pail
P-215055	55 Gallon Drum

Typical Properties:

Appearance	Bright and Clear Amber
Kinematic Viscosity @ 40°C, ASTM D445	68.0 cSt
Kinematic Viscosity @ 100°C ASTM D445	8.7 cSt
Viscosity Index, ASTM D2270	99
Flash Point, ASTM D92	228°C
Copper Strip Corrosion ASTM D130	1b
Pour Point	-18°C
Foam Tendency/Stability ASTM D892	20/0
Oxidation Stability, ASTM D943	>5000
Rust Protection, ASTM D 655B	Pass
FZG Load Support, ISO 14635, Fail Stage	13

Address: P.O. Box 1148 Pryor OK 74362 • **Toll Free:** 888-729-7787 • **Email:** info@hemsaw.com

HE&M, Inc., whose policy is one of continuous improvement, reserves the right to change the price, specifications, or design, as well as discontinue any product, at any time without notice and without incurring any obligations. Copyright 112800 HEM, Inc. All rights reserved.